



HIGH PRESSURE WASHER

High Pressure Washer Powered by Koshin Engine

- **1.5M Self Priming Guarantee (vertically 1.5M)**
Self priming pump system capable of pumping up water from any water source
- **Powered by Reliable Koshin Engine**
Koshin K180 and K210 engine for quiet, reliable performance
- **Quick Couple Nozzle Set as Standard Accessory**



5.6 HP
MAX 2180 PSI



JCE-1510UK

■ Specification

Model	JCE-1408U	JCE-1408UDX	JCE-1510UK
PUMP	Max. Pressure	14 MPa	
	Max. Volume	8 L/min	
	Recommended Feed-water	Clear water at 5 – 40 °C	
	Max. Suction Lift	1.5 m	
ENGINE	Necessary Volume of Engine Oil	120 cc	450 cc
	Type	Forced Air-Cooled 4-stroke OHV Gasoline Engine	
	Model	Koshin K180	
	Displacement	179 cc	Koshin K210
	Fuel	Automotive Unleaded Gasoline	
	Fuel Tank Capacity	3.6 L	
	Engine Oil	SAE 10W-30	
	Necessary Volume of Engine Oil	600 cc	
Accessories	1 Gun Nozzle (screw attachment type), 1 Straight/Fan shape nozzle, 1 Delivery hose (screw attachment type) (10 m), 2 Suction hoses (3 m), 1 Strainer	1 Gun Nozzle (quick attachment type), 1 Delivery hose (quick attachment type) (10 m), 2 Suction hose (3 m), 1 Strainer, 5 Interchangeable nozzle: (1) 15° (2) 25° (3) 40° (4) point-blank (5) Detergent nozzle	1 Gun Nozzle (quick attachment type), 1 Delivery hose (quick attachment type) (10 m), 2 Suction hoses (3 m), 1 Strainer, 6 Interchangeable nozzle: (1) 15° (2) 25° (3) 40° (4) point-blank (5) Detergent nozzle (6) Rotary nozzle
Net Weight	25 kg (55 lbs)	32.5 kg (72 lbs)	36 kg (79 lbs)
Gross Weight	34.5 kg (76.0 lbs)	42.5 kg (93.7 lbs)	46.0 kg (101 lbs)
Dimensions L×W×H (mm)	540 × 435 × 525	710 × 400 × 530	710 × 400 × 530
Packing Unit	1		

*Japanese domestic model